

 Bahama Breeze	 View 2	 View 3	 View 4	 View 5
 Breaking Dawn	 View 2	 View 3	 View 4	 View 5
 Calypso Bay	 View 2	 View 3	 View 4	 View 5
 Irish Mist	 View 2	 View 3	 View 4	 View 5
 Mountain Meadow	 View 2	 View 3	 View 4	 View 5
 Mystic Falls	 View 2	 View 3	 View 4	 View 5
 Northern Lights	 View 2	 View 3	 View 4	 View 5
 Razzle Dazzle	 View 2	 View 3	 View 4	 View 5
 Western Skies	 View 2	 View 3	 View 4	 View 5

Different Hues From Different Views

ALTERED FX: APPLICATION TIPS

Cohills Pro Series® Altered FX are 9 different blends of color shifting pigments, that when added to 100% solids epoxy, create a unique one of a kind floor.

An Altered FX floor will shift between three to four colors depending on different variables such as, but not limited to, the angle being viewed, lighting and application techniques. It is strongly recommended that the substrate be primed in a dark color (preferably black) to achieve the best results. Altered FX may be used in conjunction with other clear vehicles such as polyurethane, acrylic sealers and waterborne epoxies. Be sure to thoroughly read all application data on whatever vehicle you may be adding Altered FX to. Testing compatibility is always recommended.

Altered FX is conveniently packaged in pigment packs designed to be added to various sizes of 100% solids epoxy.

10 Gram Unit	32 oz.	1 Quart
40 Gram Unit	128 oz.	1 Gallon
50 Gram Unit	160 oz.	1-1/4 Gallon
60 Gram Unit	192 oz.	1-1/2 Gallon

Note: It is highly recommended that you do a sample test area before installation. The color samples shown are approximate and represent as closely as possible the appearance of Cohills Pro Series® Altered FX. The final color may not match the colors shown here due to variables beyond our control, including finishing techniques, job conditions & curing methods.

Cohills Building Specialties, Inc.®
3825 East Anne Street • Phoenix, AZ 85040
Phone: 602-266-0462 • Toll Free: 877-709-2220
©2011 All Rights Reserved Cohills Building Specialties, Inc.®
www.cohills.com