

COHILLS PRO SERIES[®] CLEAR SEAL HIGH SOLIDS

Cohills Pro Series[®] Clear Seal HS - 25% solids are solvent-acrylate based sealers for interior or exterior concrete that can be applied both vertically and horizontally. **Cohills Pro Series[®] Clear Seal HS Sealer** reduce the damage caused by salt, water, UV Light, and are highly resistant to oil and some chemicals. The glossy finish of these sealers brighten the natural coloration of aggregates, enhancing their architectural and esthetic qualities with a lustrous seal. It may also be used as a curing compound as needed.

Applications include, but are not limited to: Colored Concrete, Stamped Concrete, Curbing, Brick, Stucco, Block, Mortar, Pavers and most other cementitious material.

» Product Availability & Coverage

- **Cohills Pro Series[®] Clear Seal HS Sealer** is available in 1 gallon containers and 5 gallon pails.
- Coverage is approximately 200 - 300 square feet per gallon for the 1st coat application and 300 - 400 square feet per gallon for additional coats. Coverage may vary due to surface porosity and surface conditions. **Do not** over apply.

» Surface Preparation

Remove all dirt, dust, oil, grease, asphalt, and foreign mater. Restore surface by patching, grouting, and filling cracks and holes. Surface should be thoroughly dry and free of any moisture. Care should be taken when applying to colored concrete. Make sure surface is fully cured or coating failure, chalking, and adhesion problems will occur.

» Application

Apply **Cohills Pro Series[®] Clear Seal HS Sealer** to form a continuous, uniform film by spray or a short-nap roller with a phenolic core. Sprayer should have neoprene seals and hose. Clean all tools immediately after use with Xylene. **DO NOT OVER APPLY.** **Cohills Pro Series[®] Clear Seal HS Sealer** is a high solids coatings. Over applying the sealer may result in bubbling, coating imperfections and wasted material. Do not apply under windy conditions or in temperatures above 90° F or temperatures

» Application continued

below 45°F. **Cohills Pro Series[®] Clear Seal HS Sealer** will be ready for light foot traffic or second coat in approximately 1 hour, normal traffic within 4 - 8 hours and will achieve maximum hardness after 24 hours. Sealer will not freeze. Store with lid tightly closed.

» Precautions

- **DANGER: FLAMMABLE LIQUID**
- **RECOMMENDED USE BY PROFESSIONALS.**
- **NEVER APPLY AROUND HEAT SOURCES SUCH AS WATER HEATERS, FURNACES, ETC.**
- **AVOID CONTACT WITH SKIN AND EYES.**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING.**
- **KEEP OUT OF REACH OF CHILDREN**

» Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.

Cohills Building Specialties, Inc.

3825 East Anne Street

Phoenix, Az. 85040

Telephone: 602-266-0462

Customer Service: 877-709-2220

www.cohills.com