

## COHILLS PRO SERIES® DC-100 ACRYLIC DECK COAT

**Cohills Pro Series® DC-100** is a low VOC, non-toxic, waterborne, UV resistant, colored pool deck coating that can be used on both new or existing pool decks.

### » Product Availability & Coverage

- **Cohills Pro Series® DC-100** is available in 1 gallon containers and 5 gallon pails.
- Available in 4 colors
- Coverage is approximately 200-300 square feet per gallon per coat. Coverage may vary due to surface porosity and conditions.

### » Surface Preparation

Thoroughly clean existing pool deck using **Cohills Pro Series® Citra Pro Degreaser**. Scrub surface thoroughly and repeat until all dirt, oil and foreign materials are removed. Flush surface with fresh water, ideally a pressure washer works best. Smooth concrete may need to be profiled with **Cohills Pro Series® Super Deck Prep** to ensure proper bonding. **NOT TO BE USED ON ANY SURFACE SUBJECT TO VEHICULAR TRAFFIC.** Allow to dry for 24 hours.

Mix thoroughly before application. Cohills Pro Series® DC-100 can be thinned with water as needed for application purposes. Thin up to 1/2 pint per gallon of coating with water.

### » Application

First Coat - Apply Cohills Pro Series® with a 3/8" quality roller in a light even coat. Allow surface to dry for a minimum of 2 hours before re-coating. Second Coat - At full strength apply the second coat evenly being careful not to leave any puddles or roller marks.

**Additional coats may be required depending on surface porosity. On new decks a second coat is almost always needed. This product is not to be applied over existing solvenated products. When using multiple units, it is recommended to box (mix) all material together.**

### » Precautions

- **USE WITH ADEQUATE VENTILATION.**
- **AVOID CONTACT WITH SKIN AND EYES.**
- **KEEP FROM FREEZING.**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING.**
- **KEEP OUT OF REACH OF CHILDREN**

### » Properties

Colors	Full Range
Vehicle	Acrylic Polymer
Solids (Weight)	55-59%*
Drying Time at 75° F	Dry to Touch 2-4 hours Recoat 8 hours

**\*Values may vary with color.**

### » Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.