

COHILLS PRO SERIES[®] EZ-STAMP

Cohills Pro Series[®] EZ-Stamp Stampable Overlay is a premixed blend of special materials that when properly mixed with water and placed on an existing concrete substrate forms a thin, cementitious overlay or coating suitable for stamping or texturing, similar to a standard concrete pour. It can be used to restore or revive, old worn out concrete.

» Product Availability & Coverage

- **Cohills Pro Series[®] EZ-Stamp** is available in 50 lb. bags.
- One 50 lb bag will typically cover
 - 22 square feet @ ¼" thick
 - 11 square feet @ ½" thick

» Surface Preparation

Surface must be clean and free of all oils, grease, paint, sealers, or anything that would interfere with proper bonding. All crack repairs, scarifying and shot blasting should have taken place prior to pressure washing. All existing control and expansion joints must be honored as they will telegraph through the overlay. Pressure-wash all dust and laitents from the surface to ensure a clean surface. Achieve a SSD (Saturated Surface Dry) condition with water immediately before the installation to cool the concrete and decrease rapid hydration. No standing water should be present upon application. Before overlay placement, prime the surface generously with **Cohills Pro Series[®] EZ-Bond** Polymer using either a short napped roller or weed sprayer. One generous coat is all that is required. Make sure that no puddles are present.

» Mixing

Measure 4 to 4.5 quarts water per bag and add to the desired mixing container. Actual liquid requirements will vary depending upon climate and weather conditions. Add dry mix. Using a drill powered mixer with a paddle blade, (or for larger jobs use a large mortar mixer) mix all material at medium speed until completely lump free. Mix should be of a consistency so that it can be placed easily with a gauged rake.

» Application

PLACEMENT: Pour the material directly onto the surface immediately after mixing. Using a gauge rake set to the desired depth, rake the material out, but leave a furrow line of material to mix in with the following batch. Wear spiked overlay shoes to allow walking in the wet material.

» Application Continued

Immediately after each batch has been raked, use a trowel, float, or squeegee to remove the gauge rake lines. When the material leaves an indent but doesn't transfer to a finger when touched, it is ready for stamping or texturing. If Powdered Antiquing Release is to be used, apply just prior to stamping. If **Cohills Pro Series[®] Liquid Release** is to be used, do not apply release until immediately before the stamp is to be applied. Apply a generous amount to the stampable surface and the stamp mat as well. Do not allow puddles to form.

STAMPING/TEXTURING: Use any **Cohills Pro Series[®]** texturing mat or texture skin that does not exceed 1/2 the depth of the applied thickness. Unlike concrete, **Cohills Pro Series[®] EZ-Stamp** stampable Overlay does not require heavy pressure or extreme tamping. Apply only enough even pressure to seat the mat and provide an impression. Allow 36 hours before foot traffic. Re-cut all control joints to the original substrate to avoid cracking. Allow the overlay to cure for a minimum of 7 days, protect the surface with **Cohills Pro Series[®] Clear Seal HS**.

» Precautions

- **PRODUCT CONTAINS CEMENT & SILICA SAND-DO NOT BREATHE DUST.**
- **USE PROPER DUST MASK, GLOVES AND GOGGLES WHEN HANDLING, MIXING OR APPLYING MATERIAL**
- **AVOID CONTACT WITH SKIN AND EYES.**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING.**
- **KEEP OUT OF REACH OF CHILDREN.**

» Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.