

## COHILLS PRO SERIES® FINAL FINISH

**Cohills Pro Series® Final Finish** is a high gloss, non yellowing & non-toxic acrylic floor finish for use on all types of sealed floors. It not only dries to a high gloss finish, it can be maintained by spray buffing. **Cohills Pro Series® Final Finish** is used to maintain floors in a brilliant polished condition with minimum labor. All types of sealed concrete floors will improve their appearance and decrease maintenance costs with the use of **Cohills Pro Series® Final Finish**.

### » Product Availability & Coverage

- **Cohills Pro Series® Final Finish** is available in 1 gallon containers, 5 gallon pails
- Product coverage is approximately 1200 sq. ft per gallon.

### » Surface Preparation & Application

Remove old polish thoroughly by scrubbing with **Cohills Pro Series® CitraPro**. Rinse floor well and let dry completely. Spread **Cohills Pro Series® Final Finish** in a thin even coat over the floor using a Lambs wool applicator or a clean finish mop. Allow to dry completely, about 25 to 30 minutes. Apply a second coat and let dry completely before allowing traffic on the floor. Damp mop with a neutral detergent as required and burnish regularly to restore the wet look. In high traffic areas, damp mop and apply a touch up coat of **Cohills Pro Series® Final Finish** as required.

No stripping is necessary before re-coating. **Spray Buffing:** Dilute 1 part of **Cohills Pro Series® Final Finish** with 3 parts of water. Using a Trig Mist sprayer, mist lightly over a 1 sq. meter (10 sq. ft.) area and buff with a polishing pad until all liquid disappears and a brilliant shine appears. Repeat this until the entire floor is renovated and polished. **Maintenance:** Occasional damp mopping with a neutral detergent will maintain the smooth glossy surface. In Heavy Traffic areas, after mopping and rinsing, let dry and apply a thin coat of **Cohills Pro Series® Final Finish**.

### » Maintenance

Occasional damp mopping with a neutral detergent will maintain the smooth glossy surface. In Heavy Traffic areas, after mopping and rinsing, let dry and apply a thin coat of **Cohills Pro Series® Final Finish**.

### » Properties

Type	Acrylic Floor Polish
Color	Colorless, non-yellowing
Odor	Mild
Toxicity	Non-toxic
Flammability	Non-Flammable
Composition	Acrylic polymer emulsion, ethylene copolymers, proprietary additives and quality control agents.

### » Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.