

COHILLS PRO SERIES[®] CLEAR SEAL HIGH SOLIDS

Cohills Pro Series[®] Clear Seal HS - 25% solids are solvent-acrylate based sealers for interior or exterior concrete that can be applied both vertically and horizontally. Cohills Pro Series[®] Clear Seal HS Sealer reduce the damage caused by salt, water, UV Light, and are highly resistant to oil and some chemicals. The glossy finish of these sealers brighten the natural coloration of aggregates, enhancing their architectural and esthetic qualities with a lustrous seal. It may also be used as a curing compound as needed.

Applications include, but are not limited to: Colored Concrete, Stamped Concrete, Curbing, Brick, Stucco, Block, Mortar, Terrazzo, Pavers and most other siliceous material.

Product Availability & Coverage

- Cohills Pro Series[®] Clear Seal HS Sealer is available in 1 gallon containers and 5 gallon pails.
- Coverage is approximately 200 - 300 square feet per gallon for the 1st coat application and 300 - 400 square feet per gallon for additional coats. Coverage may vary due to surface porosity and surface conditions. Do not over apply.

Surface Preparation & Application

Remove all dirt, dust, oil, grease, asphalt, and foreign mater. Restore surface by patching, grouting, and filling cracks and holes. Surface should be thoroughly dry and free of any moisture. Care should be taken when applying to colored concrete. Make sure surface is fully cured or coating failure, chalking, and adhesion problems will occur. Apply Cohills Pro Series[®] Clear Seal HS Sealer to form a continuous, uniform film by spray or a short-nap roller with a phenolic core. Sprayer should have neoprene seals and hose. Clean all tools immediately after use with Xylene.

DO NOT OVER APPLY. Cohills Pro Series[®] Clear Seal HS Sealer is a high solids coatings. Over applying the sealer may result in bubbling, coating imperfections, and wasted material. Do not apply under windy conditions or in temperatures above 90°F or temperatures below 45°F. Cohills Pro Series[®] Clear Seal HS Sealer will be ready for light foot traffic or second coat in approximately 1 hour, normal traffic within 4 - 8 hours and will achieve maximum hardness after 24 hours. Sealer will not freeze. Store with lid tightly closed.

Precautions:

- **DANGER: FLAMMABLE LIQUID**
- Recommended for use only by professionals.
- Never apply around heat sources such as water heaters, furnaces, etc.
- Cohills Pro Series[®] Clear Seal HS Sealer should be used in well ventilated areas.
- Prior to use or handling of material consult Material Safety Data Sheet.

VOC Compliance:

Cohills Pro Series[®] Clear Seal HS Sealer meets and exceed VOC rules as written under the Clean Air Act. Contains less than 5.8 pounds per gallon/700 grams per liter Volatile Organic Compounds as required for a Concrete Cure and Seal Ready to use. No mixing required. Shipping Information is as follows: Coating Solution, 3, UN1139, PG II, Flammable Liquid.

Cohills Building Specialties, Inc.
3825 East Anne Street
Phoenix, Az. 85040
Telephone: 602-266-0462
Customer Service: 877-709-2220
www.cohills.com

Cohills Pro Series[®] Clear Seal HS Sealer available through: