

COHILLS PRO SERIES[®] LIQUID RELEASE

Cohills Pro Series[®] Liquid Release is a clear parting agent specifically designed to keep mats and stamping tools from sticking to the still wet concrete. These parting agents create a barrier between the mat and the concrete surface, allowing a clean, non-staining, non-sticking surface every time. This exclusive formula contains mild chemicals and additives that not only prevent damage to the mat or stamp, but help to prolong their life expectancy as well. **Cohills Pro Series[®] Liquid Release** may be used on all types of concrete surfaces including but not limited to polymer overlays, concrete countertops, textured or stenciled concrete surfaces, etc. Designed for use on both interior and exterior surfaces, this clear formula has a pleasant bubble gum odor and will fully evaporate at a slow rate leaving absolutely no residue behind.

» Product Availability & Coverage

- **Cohills Pro Series[®] Liquid Release** is available in 1 gallon containers and 5 gallon pails
- Product coverage is approximately 250 sq. ft per gallon.

» Application

- Using a pump sprayer, apply a generous amount of **Cohills Pro Series[®] Liquid Release** to the still wet surface. Apply material to a small area (approximately 10 - 15 sq. ft.) to ensure the best results. If used in too large of an area, the material may evaporate before the mats can be placed on the concrete. This will result in poor release and wasted material.
- Release will evaporate and leave no residue on the concrete surface.
- Powdered color release agents may be incorporated into the solution and sprayed. This method requires constant agitation of the material to keep the powdered release agent properly dispersed.

» Precautions

- **DANGER: FLAMMABLE LIQUID**
- **NEVER APPLY AROUND HEAT SOURCES SUCH AS WATER HEATERS, FURNACES, ETC.**
- **AVOID CONTACT WITH SKIN AND EYES.**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING.**
- **KEEP OUT OF REACH OF CHILDREN**

» Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.