

COHILLS PRO SERIES[®] NEW CANVAS

Cohills Pro Series[®] New Canvas is a cementitious based; polymer modified decorative concrete micro-topping that closely resembles the look of natural concrete. Cohills Pro Series[®] New Canvas is used to re-surface concrete that is worn, pitted or spalled, virtually creating a “new canvas” to apply your choice of stain or to retain the look of natural concrete. Cohills Pro Series[®] New Canvas is ideal for use on existing interior or exterior horizontal concrete surfaces such as patios, walkways, driveways, garage floors and most other residential or commercial concrete surfaces.

Product Availability & Coverage

- Cohills Pro Series[®] New Canvas is available in both Gray and White.
- One 50 pound bag yields approximately 100-200 square feet when applied on a smooth surface. Actual coverage will vary depending on texture of substrate and method of application.

Surface Preparation:

The concrete surface should be free of unbound cementitious byproducts, loose dirt, oil, grease, or other contamination. Any animal fats or petroleum oils should be removed with a CONCRETE CLEANER & DEGREASER. Exterior surfaces should be acid etched using a 5 to 1 solution of water to muriatic acid. Interior surfaces should be prepared by mechanical means (shot-blast, sand-blast or by rotary sander).

One 50 pound bag of Cohills Pro Series[®] New Canvas will require approximately 7 quarts of water. For best results use a 1/2 inch drill with a Jiffy type mixing paddle. Add the measured water to a clean 5 - gallon pail. With the mixer running, slowly add the Cohills Pro Series[®] New Canvas powder, mixing until a lump free consistency is obtained. Allow the mixed material to set, or slake for approximately 5 minutes and then re-mix prior to placement.

Precautions:

Product contains Portland cement and silica sands. Do not breathe in dust. Use proper dust masks, gloves and goggles when handling, mixing or applying material. Avoid eye and skin contact. Wash exposed skin promptly with water. May cause skin irritation and cement burns. In case of eye contact, flush immediately with water and contact a physician. Read MSDS prior to use.

IMPORTANT NOTICE

THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANT ABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NONCONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, OF WHICH HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

Cohills Building Specialties, Inc.
3825 East Anne Street
Phoenix, Az. 85040
Telephone: 602-266-0462
Customer Service: 877-709-2220
www.cohills.com

Cohills Pro Series[®] New Canvas is available through: