

COHILLS PRO SERIES® WB SEALER

Cohills Pro Series® WB Sealer is a single component waterborne acrylic sealer. It is low VOC and UV stable making it an ideal choice for interior and exterior projects. COHILLS PRO SERIES® WB SEALER is available in gloss and satin (flat) finishes.

Applications include, but are not limited to: Colored Concrete, Stamped Concrete, Curbing, Brick, Stucco, Block, Mortar, Pavers and most other cementitious material.

» Product Availability & Coverage

- Cohills Pro Series® WB Sealer is available in 1 gallon and 5 gallon containers.
- Coverage is approximately 300 square feet per gallon per coat. Coverage may vary due to surface porosity and conditions.

» Surface Preparation

Remove all dirt, dust, oil, grease and foreign matter. Surface should be thoroughly dry and free of any moisture. Make sure surface is fully cured or coating failure and adhesion problems will occur.

» Application

Apply COHILLS PRO SERIES® WB SEALER to form a continuous uniform film using a sprayer or a short-nap roller. DO NOT OVER APPLY. Do not apply under windy conditions or in temperatures above 90° F or temperatures below 50° F.

» Precautions

- **USE WITH ADEQUATE VENTILATION.**
- **AVOID CONTACT WITH SKIN AND EYES.**
- **KEEP FROM FREEZING**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING.**
- **KEEP OUT OF REACH OF CHILDREN**

» Properties

Appearance	Milky White
Gloss	Full Range
Solids (Volume)	30-31%
Solids (Weight)	34-35%
VOC	<50 g/l
Drying Time at 75° F	30-minutes to touch 1-hour to recoat 4-hours Light foot traffic Heavy traffic in 24-hours Full cure in 48-hours

» Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.

Cohills Building Specialties, Inc.

3825 East Anne Street

Phoenix, Az. 85040

Telephone: 602-266-0462

Customer Service: 877-709-2220

www.cohills.com