

## COHILLS PRO SERIES® EARTH STAIN

**Cohills Pro Series® Earth Stains** are a line of water based, non-acid polymer bonded stains that penetrate into the concrete surface to produce a vibrant long lasting UV resistant concrete surface.

### » Product Availability & Coverage

- **Cohills Pro Series® Earth Stain** is a concentrate and packaged in 1 quart containers.
- Product coverage is approximately 125-250 sq. ft. per gallon depending on application technique and/or surface conditions.

### » Surface Preparation

**IMPORTANT:** It is always recommended that a small out-of-the-way section of your project be used for test section. A new concrete slab should be cured for four (4) weeks. The optimum time to stain in a new home is after all construction (taping, texturing and painting) is completed and just prior to the base-boards being affixed. We recommend that you protect your new slab during the construction phase with plastic, paper, cardboard, plywood or sheet rock covering as the initial cleaning step will be much easier. All trades should be advised that the slab will be the finished floor. The concrete surface must be clean and free of paints, wax, grease, dirt and any other contaminants. Clean the floor with **Cohills Pro Series® Super Deck Prep**. Use 1 part Cohills Pro Series® Super Deck Prep to 1 part water. Apply to surface and scrub entire area to be stained. Flush thoroughly with clean water leaving no residue. \*Hard surfaces may need to be treated a second time or **Cohills Pro Series® Super Deck Prep** used at full strength. (If applying full strength-test small area) Next use **Cohills Pro Series® Citra Pro** at a dilution of 1 part Citra Pro to 4 parts water. Apply to surface, scrub and rinse thoroughly. Allow surface to dry before applying stain.

### » Application

**1 quart of concentrate makes 1 gallon of stain.**

Mixing Instructions: Empty entire quart into pump can sprayer or separate bucket. Add exactly 3 quarts of clean filtered or distilled water. Shake or stir well prior to application. **\*\*\*DO NOT ADD MORE THEN 3 QUARTS OF WATER\*\*\***

Apply Cohills Pro Series® Stain with plastic sprayer or sponge in the technique of your choice. Allow to dry thoroughly. Drying time will vary according to surface

### » Application continued

conditions and humidity. Once dry, the stain is water resistant. Apply sealer to enrich and protect your finished project.

Clean up: Discard brush or application utensil in an appropriate manner or clean thoroughly with soap and water.

Due to variations in concrete composition, age, surface conditions, surface preparation and application techniques exact color will vary from project to project.

### » Precautions

- **AVOID CONTACT WITH SKIN AND EYES**
- **KEEP FROM FREEZING**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING**
- **KEEP OUT OF REACH OF CHILDREN**

### » Properties

Type	Non-acid, polymer bonded concrete stain
Colors	Various
Odor	Slight
Toxicity	Low. Harmful if swallowed
VOC	Low. Less than 100gm/L
Flammability	Non-Flammable

### » Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller, nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.

\*Refer to Cohills® Technical Bulletin CBS082013 Warranty-Disclaimer-Precautions for additional information.