

## COHILLS PRO SERIES<sup>®</sup> EZ-DECK

**Cohills Pro Series<sup>®</sup> EZ-Deck** is a single component polymer modified cementitious material. **Cohills Pro Series<sup>®</sup> EZ-Deck** may be sprayed, troweled or squeegee applied to create a multitude of decorative finishes. **Cohills Pro Series<sup>®</sup> EZ-Deck** may be colored, stained, painted or sealed with a variety of **Cohills<sup>®</sup>** products.

### » Product Coverage

- Coverage will vary depending upon application methods and techniques. When sprayed, **Cohills Pro Series<sup>®</sup> EZ-Deck** will yield approximately 150-200 sq. ft. per 50 lb. bag.

### » Surface Preparation

A properly prepared surface is paramount to the success of any coating. Any existing coatings such as curing agents or sealers must be removed. Any spalling or cracking must be addressed in order to insure a structurally sound substrate. Only structurally sound, clean substrates are considered candidates for **Cohills Pro Series<sup>®</sup> EZ-Deck**. Typical methods of preparation include, but are not limited to: grinding, shot blasting, scraping, acid washing and de-greasing.

### » Mixing Instructions

A 50 lb. bag of **Cohills Pro Series<sup>®</sup> EZ-Deck** mixes with approximately 4 – 5 quarts of clean water (depending on application method, substrate, air temperature etc.) The designated amount of water should be placed in a clean 6 gallon bucket. Next, **Cohills Pro Series<sup>®</sup> EZ-Deck** should be slowly introduced to the water while using a ½ inch drill with a mixing paddle. Once a lump free consistency is achieved, allow the mixed material to set/slake for approximately 5 minutes. Re-mix material prior to placement.

### » Precautions

- **PRODUCT CONTAINS CEMENT & SILICA SAND. DO NOT BREATHE DUST**
- **USE PROPER DUST MASK, GLOVES AND GOGGLES WHEN HANDLING, MIXING OR APPLYING MATERIAL**
- **AVOID CONTACT WITH SKIN AND EYES.**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING**
- **KEEP OUT OF REACH OF CHILDREN**

### » Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller, nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.

\*Refer to **Cohills<sup>®</sup> Technical Bulletin CBS082013 Warranty-Disclaimer-Precautions** for additional information.

---

#### Manufactured for:

**Cohills Building Specialties, Inc.**

**3825 East Anne Street**

**Phoenix, Az. 85040**

**Telephone: 602-266-0462**

**Customer Service: 877-709-2220**

**www.cohills.com**