

COHILLS PRO SERIES® RELEASE AGENT

Cohills Pro Series® Release Agent is a dry blend of iron oxide and color pigments designed to allow the clean release of texturing tools from the concrete surface. In addition to providing a clean release, it also adds color variation to the textured surface, thus providing an antiquing effect. **Cohills Pro Series® Release Agent** may be used on gray concrete, interior colored concrete and color hardened surfaces.

» Product Availability & Coverage

- **Cohills Pro Series® Release Agent** is available in 25 standard colors and is packaged in 1 gallon containers and 5 gallon pails.
- Product coverage varies according to intended use & color. 1,000-1,200 sq. ft. per 30 lb pail.

» Application

The surface is ready for release agent once the concrete reaches the point when no bleed water remains on the surface and when the concrete is sufficiently firm to withstand texturing tools and the weight of a work crew. **Cohills Pro Series® Release Agent** should be evenly hand-broadcast over the entire surface of freshly placed concrete.

Cohills Pro Series® Release Agent should remain in the dry state on the concrete surface **IT SHOULD NOT BE WORKED INTO THE SURFACE. Care should be taken not to trowel the powder into the wet concrete, which could cause the surface to have permanent discoloration.**

Cohills Pro Series® Release Agent may be removed as soon as the concrete has hardened to the point that it will not scratch (normally two to three days). Pressure washing the surface is an effective way to remove the excess release as well as scrubbing with a stiff bristle broom.

» Application continued

Inconsistencies in job site conditions, finishing practices and curing methods may produce variations in the color of the finished product. **Cohills Pro Series® Release Agent** may be used on vertical faces of step risers, curb, etc., but is not practical for use on large areas of vertical surfaces.

» Precautions

- **PRODUCT CONTAINS CEMENT & SILICA SAND DO NOT BREATHE DUST**
- **USE PROPER DUST MASK, GLOVES AND GOGGLES WHEN HANDLING, MIXING OR APPLYING MATERIAL**
- **AVOID CONTACT WITH SKIN AND EYES**
- **READ MATERIAL SAFETY DATA SHEET BEFORE USING**
- **KEEP OUT OF REACH OF CHILDREN**

» Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither the seller, nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective and must be received in writing within (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.

***Refer to Cohills® Technical Bulletin CBS082013 Warranty-Disclaimer-Precautions for additional information.**